

# KEOR LINE RT

SINGLE-PHASE  
UPS  
from 1000 to 3000 VA





# KEOR LINE RT

Convertible UPS that can  
be used in both tower  
and rack configurations

- Sinusoidal output
- Convertible display for tower and rack configurations
- Advanced control interface
- Emergency shutdown remotely
- Microprocessor control
- MODEM/LAN telephone protection
- RS-232 or USB interface
- Cold start function
- Protection against voltage peaks
- Integrated self-diagnostics
- Intelligent battery management
- Overload and short-circuit protection
- Excellent voltage regulation

# KEOR LINE RT

## Line Interactive UPS - Single phase VI-SS




3 100 45

Pack	Cat. Nos.	UPS				
		NOMINAL POWER VA	ACTIVE POWER W	BACKUP TIME (min)	NO. OF SOCKETS IEC (10A/16A)	COMMUNICATION PORTS
	<b>3 100 45</b>	1000	900	10	8/-	USB-RS232
	<b>3 100 46</b>	1500	1350	8	8/-	USB-RS232
	<b>3 100 47</b>	2200	1980	8	8/1	USB-RS232
	<b>3 100 48</b>	3000	2700	8	8/1	USB-RS232


Cat. Nos.	3 100 45	3 100 46	3 100 47	3 100 48
<b>General characteristics</b>				
Nominal power (VA)	1000	1500	2200	3000
Active power (W)	900	1350	1980	2700
Technology	Line interactive VI-SS			
Waveform	Sinusoidal			
<b>Input characteristics</b>				
Input voltage	230 V ± 10 %			
Input frequency	45-65 Hz			
Input voltage range	165 V-300 V			
<b>Output characteristics</b>				
Output voltage	230 V ± 10 %			
Output frequency (nominal)	50/60 Hz +/-0,5 % autosensing			
THD of output voltage	< 3 % with linear load			
<b>Batteries</b>				
Number of batteries	3	3	6	6
Battery range type/voltage	12 V, 7 Ah	12 V, 9 Ah	12 V, 7 Ah	12 V, 9 Ah
<b>Communication and management</b>				
Screen and signalling	Three buttons, display and three LEDs for real-time control of the status of the UPS			
Telephone protection	RJ11/RJ45			
Remote control	SNMP Slot			
<b>Mechanical characteristics</b>				
Dimensions W x D x H (mm)	440x405x88		440x650x88	
Net weight (kg)	19	20	34	37
<b>Ambient conditions</b>				
Ambient operating temperature (°C)	0 ÷ 40 °C			
Relative humidity (%)	0÷95 % non-condensing			
Noise at 1 m (dBA)	< 40			
<b>Certifications</b>				
Reference product standards	EN62040-1, EN62040-2, EN62040-3			

**NOTE:** The stated back-up times in minutes are estimated and may vary according to the load characteristics, operating conditions and environment.

1000-1500 VA



2200-3000 VA





**World Headquarters and  
International Department**  
87045 Limoges Cedex - France  
☎ : + 33 (0) 5 55 06 87 87  
Fax : + 33 (0) 5 55 06 74 55

---

In accordance with its policy  
of continuous improvement, the  
Company reserves the right to change  
specifications and designs without  
notice. All illustrations, descriptions,  
dimensions and weights in this  
catalogue are for guidance and cannot  
be held binding on the Company.